

From Sunlight to Electricity



Deutsches Zentrum für Luft- und Raumfahrt e.V.
German Aerospace Center

Institute of Technical Thermodynamics


Stuttgart, Germany

<http://www.dlr.de/tt>


From Sunlight to Electricity

Step 1:

Sunlight is Concentrated by Parabolic Mirrors that Continuously Follow the Sun's Position on the Sky




Parabolic Trough Concentrator




From Sunlight to Electricity

Step 2:

The Concentrated Solar Heat is Absorbed by a Steel Tube and Transported away by a Fluid that is Circulated within the Tube



Heat Collecting Element with Absorber Tube and Evacuated Glass Tube



- 1 Glass-Metal-Connection
- 2 Glass Envelope
- 3 Anti-Reflective Coating
- 4, 5 Getter

- 6 Steel Tube
- 7 Expansion Bellows
- 8 Evacuated Space
- 9 Solar Coating

From Sunlight to Electricity



Step 3:

The Hot Fluid is Gathered from a Large Field of Solar Concentrating Collectors and then is Pumped to a Central Heat Exchanger


Parabolic Trough Collector Field




From Sunlight to Electricity

Step 4:

Within the Heat Exchanger, the Hot Fluid Generates Superheated Steam with over 100 bar Pressure




Solar Steam Generator



From Sunlight to Electricity

Step 5:


The Superheated Steam Activates the Turbine and the Electricity Generator of a Steam Cycle Power Plant



From Sunlight to Electricity

Option 1:


Solar (only) Electricity Generating System



From Sunlight to Electricity

Option 2:


Hybrid (solar & fuel) Electricity Generating System



From Sunlight to Electricity

Option 3:


Solar/Hybrid Electricity Generating System
with Thermal Energy Storage



From Sunlight to Electricity

Option 4:


Solar/Hybrid Co-Generation of Electricity and Heat for Seawater Desalination



From Sunlight to Electricity

Option 5:

Solar/Hybrid Co-Generation of Electricity and Heat for District Cooling



From Sunlight to Electricity



Operating Experience:

Parabolic Trough Plants in Kramer Junction, Dagget and Harper Lake, California



354 MW_e Installed Capacity

Commercial Operation since 1986

More than 1 Billion US\$ Turnover

Steam at 390 °C, 100 bar

From Sunlight to Electricity



Recent Highlights:

Direct Steam Parabolic Trough Demonstration
at Plataforma Solar de Almeria, Spain



Demonstration of Direct
Superheated Steam Generation
in Parabolic Trough Collectors

Steam at 400 °C, 100 bar
(550 °C, 120 bar projected)

From Sunlight to Electricity



Recent Highlights:

Demonstration of Pressurized Air Receiver for Gas Turbine Operation at Plataforma Solar de Almeria, Spain



Demonstration of Pressurized Volumetric Air Receiver for Gas Turbines and Combined Cycles

Air at 850 °C, 15 bar
(1200 °C, 20 bar projected)



From Sunlight to Electricity



Recent Highlights:

NEVAG's Foldable Parabolic Trough Collector „Synthesis Solar“




Less Wind Load,
Automatic Washing and
Water Recycling in
Closed Position

From Sunlight to Electricity



Recent Highlights:

Demonstration of Solarmundo's Advanced Solar Concentrating System at Liege, Belgium



Demonstration of Direct Steam Generation in Fresnel Collector

Steam at 500 °C, 100 bar projected

From Sunlight to Electricity



Solar Thermal Power Projects:

From Basic Information to Commissioning


	Project Definition		Engineering, Procurement, Construction		Operation
	3 M	first year	second year	third year	30 - 40 years
Basic Project Information	■				
Project Assessment		■			
Project Definition		■			
Purchase of Land			■		
Engineering			■		
Procurement			■		
Civil Works			■		
Construction				■	
Commissioning				■	
Operation and Maintenance					■

From Sunlight to Electricity



Project Assessment Phase

Gathering Basic Data and Comparing Investment Opportunities




- Basic Project Information
- Finance of Project Studies
- Solar Resource Assessment
- Site Ranking
- Comparison of Project Alternatives

From Sunlight to Electricity

Project Definition Phase

In-Depth Studies and Decisions on Investment, Technology, Site, Project Consortium and Scheme of Finance



Project Company

Licensing Negotiations

Site Selection

Performance Model

EPC Contract

Project Consortium

From Sunlight to Electricity



Engineering, Procurement & Construction Phase

Finance, Insurance and Realisation
of Power Plant Construction Phase



Construction Loan

Detailed Engineering

Procurement of Equipment

Civil Works & Construction

Commissioning & Grid
Synchronisation

From Sunlight to Electricity



Operation Phase

Electricity, Desalted Water and District Cooling
from a Regional Resource with no Pollution or Cost Escalation



Public Utility

Independent Power Producer

Power Purchase Agreement


Acceptable Rate of Return

Build, Own, Operate, Transfer

From Sunlight to Electricity

Economics:

Fuel Resources are replaced by Capital Goods.
This means higher Investment.




Investment Structure of
Power Plants with 200 MW
Capacity and 190,000 m³/d
Seawater Desalination

From Sunlight to Electricity



Economics:

Fuel Resources are replaced by Capital Goods.
This means higher Investment and Capital Cost,
but lower Fuel Cost and Cost Escalation



Annual Balance of
Power Plants with 200 MW
Capacity and 190,000 m³/d
Seawater Desalination

Cost:

Electricity	0.055 €/kWh
Water	1.50 €/m ³
Fuel Oil	0.80 €/gal